



# IN THE UNITED STATES PATENT AND TRADEMARK OFFICE BEFORE THE BOARD OF PATENT APPEALS AND INTERFERENCES

In re application of

Docket No. Q76774

Hiroyuki HASEBE, et al.

Appln. No. 10/633,693

Group Art Unit: 2875

Confirmation No. 7610

Examiner: Minh, A.

Filed: August 5, 2003

For:

DISCHARGE LAMP LIGHTING DEVICE

#### SUBMISSION OF APPEAL BRIEF

#### **MAIL STOP APPEAL BRIEF - PATENTS**

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

Submitted herewith please find an Appeal Brief. A check for the statutory fee of \$500.00 is attached. The USPTO is directed and authorized to charge all required fees, except for the Issue Fee and the Publication Fee, to Deposit Account No. 19-4880. Please also credit any overpayments to said Deposit Account. A duplicate copy of this paper is attached.

Respectfully submitted,

Billy Contr Rauleur

SUGHRUE MION, PLLC

Telephone: (202) 293-7060

Facsimile: (202) 293-7860

washington office 23373

CUSTOMER NUMBER

Date: August 2, 2005

Billy Carter Raulerson Registration No. 52,156



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE BEFORE THE BOARD OF PATENT APPEALS AND INTERFERENCES

Docket No. Q76774

Hiroyuki HASEBE, et al.

Appln. No. 10/633,693

In re application of

Group Art Unit: 2875

Confirmation No. 7610

Examiner: Minh, A.

Filed: August 5, 2003

For:

DISCHARGE LAMP LIGHTING DEVICE

APPEAL BRIEF UNDER 37 C.F.R. § 41.37

**MAIL STOP APPEAL BRIEF - PATENTS** 

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

In accordance with the provisions of 37 C.F.R. § 41.37 Appellant is submitting an Appeal Brief to appeal from the final Office Action dated February 9, 2005 (hereinafter "the final Office Action), wherein claims 1-3 are rejected.¹ This Appeal Brief is accompanied by a Submission which includes the required appeal fee set forth in 37 C.F.R. § 41.20(b)(2). Appellant's Notice of Appeal was filed on June 9, 2005. Therefore, the present Appeal Brief is timely filed.

08/03/2005 SZEWDIE1 00000007 10633693

01 FC:1402

500.00 DP

<sup>&</sup>lt;sup>1</sup> Claims 1-3 have been twice rejected and, thus, are ripe for appeal.

# **Table of Contents**

I.	REAL PARTY IN INTEREST	3
I <b>I</b> .	RELATED APPEALS AND INTERFERENCES	4
III.	STATUS OF CLAIMS	5
IV.	STATUS OF AMENDMENTS	<i>6</i>
V.	SUMMARY OF THE CLAIMED SUBJECT MATTER	7
VI.	GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL	9
VII.	. ARGUMENT	10
CL	AIMS APPENDIX	12
EV	IDENCE APPENDIX:	13
REI	LATED PROCEEDINGS APPENDIX	14

## I. REAL PARTY IN INTEREST

The real party in interest is MITSUBISHI DENKI KABUSHIKI KAISHA (Assignee) by virtue of an assignment executed by the inventors (Appellant), on September 22, 2003, and recorded by the Assignment Branch of the U.S. Patent and Trademark Office on December 11, 2003 (at Reel 014780, Frame 0775).

## II. RELATED APPEALS AND INTERFERENCES

Upon information and belief, there are no other prior or pending appeals, interferences, or judicial proceedings known to Appellant, Appellant's representatives or the Assignee that may be related to, be directly affected by, or have a bearing on the Board's decision in this appeal.

#### III. STATUS OF CLAIMS

The present application was filed on August 5, 2003 with original claims 1-3. Claim 1 was amended in an Amendment Under 37 C.F.R. § 1.111 filed on November 18, 2004. No subsequent amendments were made to the claims.

Accordingly, claims 1-3 are the claims currently pending in the application. Claims 1-3, which have each been at least twice rejected, are the claims on appeal (see Claims Appendix).

# IV. STATUS OF AMENDMENTS

No amendments have been filed subsequent to a final rejection.

#### SUMMARY OF THE CLAIMED SUBJECT MATTER

#### Background

Among discharge lamps, high-intensity discharge lamps (HID bulbs) such as a metal halide bulb, a high-pressure sodium bulb, and a mercury bulb have been used as illuminating lamps (e.g., in streetlamps), because the high-intensity discharge lamps provide wide light flux, high lamp efficiency, long life, etc. (Appellant's specification: p. 1, lns. 11-19).

To switch on a discharge lamp (bulb) of this type, starting pulses of a high voltage are superposed on a predetermined voltage applied to the bulb at the time of starting the bulb (Appellant's specification: p. 1, lns. 20-25). Therefore, a DC/DC converter and an inverter are provided for lighting the bulb stably, while an igniter (starter) is provided for generating the high-voltage pulses (*Id.*).

In particular, the polarity of a voltage Va output from the DC/DC converter 3, which is supplied with an input voltage from a DC power source 1 (e.g., a car battery), is inverted periodically so that rectangular AC voltages (Vc and Vd) are applied to the bulb 6 (Appellant's specification: p. 2, lns. 4-19; and Figs. 5 and 6). The voltages Vc and Vd are formed as negative voltages to prevent devitrification of metal enclosed in the bulb 6 (Id.).

In related-art discharge lamps, all electric power supplied to the bulb is electric power output from the DC/DC converter (Appellant's specification: p. 3, lns. 10-19). Therefore, the output capacity of the DC/DC converter must be designed according to the amount of electric power required for switching on the bulb (Id.). Consequently, in a discharge lamp lighting

7

device (e.g., a car headlamp) requiring high electric power at the initial stage of lighting, it was not possible to reduce the size of the DC/DC converter (Id.).

#### Claims 1-3

The present invention provides a discharge lamp lighting device in which a reduction in size (and cost) can be attained (Appellant's specification: p. 3, lns. 22-24). In an exemplary embodiment of the present invention, a discharge lamp is supplied with (1) electric power of a negative voltage boosted by a DC/DC converter and (2) electric power of a positive voltage given directly from a DC source (Appellant's specification: p. 4, lns. 1-3; and claim 1).

Furthermore, the electric power of the positive voltage may be given from the DC source through a voltage drop circuit (Appellant's specification: p. 4, lns. 4-5; and claim 2).

Additionally, this voltage drop circuit may include an inverter (Appellant's specification: p. 4, ln. 6; and claim 3).

#### Means-Plus-Function Claims

No means-plus-function or step-plus-function have been identified among the claims on appeal.

# VI. GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL

1. Claims 1-3 are rejected under 35 U.S.C. § 102(e) as allegedly being anticipated by

U.S. Patent No. 6,489,732 to Ito et al. (hereinafter "Ito").

#### VII. ARGUMENT

It is respectfully submitted that appealed claims 1-3 are not anticipated by Ito for at least the following reasons. Accordingly, Appellant respectfully requests that the members of the Board reverse the Examiner's rejection of these claims.

Claim 1, which is the sole independent claim, recites, *inter alia*, that "said inverter inverts the polarity of a sum of a negative voltage boosted by said DC/DC converter and a positive voltage given from said DC source to generate an AC wave." Thus, in claim 1, the recited sum has two components: (1) a negative voltage boosted by the DC/DC converter and (2) a positive voltage given from the DC source.

The Examiner alleges that Ito discloses these recited components (the final Office Action: page 2; *citing* Ito: Fig. 1; col. 2:47-67 and col. 8:1-63). To the contrary, in Ito, the sole connection to the power source 2 is the line on which the voltage *Vin* from the power source 2 is provided to a DC power source circuit 3 (Ito: Fig. 1; and col. 2:47-67). The DC power source circuit 3 includes two DC-DC converters (*Id.*). A first DC-DC converter 3A generates a positive polarity output from *Vin*, while a second DC-DC converter 3B generates a negative polarity output from *Vin* (*Id.*).

Ito fails to disclose or suggest that a positive voltage given from the power source 2 (along with a negative voltage boosted by a DC-DC converter) are both used in the generation of an AC voltage. Instead, in Ito, the positive polarity output Vdcp, like the negative polarity output voltage Vdcn, is output from a DC-DC converter and is <u>not</u> provided from the power source 2.

APPEAL BRIEF UNDER 37 C.F.R. § 41.37

U.S. Application No. 10/633,693

Attorney Docket No. Q76774

Indeed, according to Ito, power sources, the voltages of which are the same, are used on

both a positive side (to1) and a negative side (to2). Conversely, according to claim 1, a positive

side voltage is set to the DC source (e.g., the battery) voltage.

Accordingly, Ito fails to disclose each and every feature recited in claim 1. Therefore,

claim 1 is not anticipated by Ito. It follows that claims 2 and 3 are not anticipated by Ito, at least

by virtue of their dependency.

In conclusion, for the reasons set forth above, Appellant respectfully requests the

members of the Board to reverse the rejections of the appealed claims and to find each of the

claims allowable as defining subject matter that is patentable over the art of record.

Unless a check is submitted herewith for the fee required under 37 C.F.R. §41.37(a) and

1.17(c), please charge said fee to Deposit Account No. 19-4880.

The USPTO is directed and authorized to charge all required fees, except for the Issue

Fee and the Publication Fee, to Deposit Account No. 19-4880. Please also credit any

overpayments to said Deposit Account.

Respectfully submitted,

Billy Carter Raulerson

Registration No. 52,156

Billy Cart Kaulerson

SUGHRUE MION, PLLC

Telephone: (202) 293-7060

Facsimile: (202) 293-7860

WASHINGTON OFFICE

23373

CUSTOMER NUMBER

Date: August 2, 2005

11

APPEAL BRIEF UNDER 37 C.F.R. § 41.37

U.S. Application No. 10/633,693

Attorney Docket No. Q76774

#### **CLAIMS APPENDIX**

**CLAIMS 1-3 ON APPEAL:** 

1. A discharge lamp lighting device comprising:

a DC/DC converter for boosting electric power given from a DC source;

an inverter; and

an igniter,

wherein said inverter inverts the polarity of a sum of a negative voltage boosted by said

DC/DC converter and a positive voltage given from said DC source to generate an AC wave, and

wherein said igniter receives said AC wave and supplies a high voltage to said discharge

lamp at a time of switching on said discharge lamp.

2. The discharge lamp lighting device according to Claim 1, further comprising a

voltage drop circuit through which electric power of a positive voltage is given from said DC

source.

3. The discharge lamp lighting device according to Claim 2, wherein said voltage

drop circuit includes an inverter.

12

# **EVIDENCE APPENDIX:**

NONE.

# RELATED PROCEEDINGS APPENDIX

NONE.